

∞ Infinity ACLS



KEY FEATURES

- Brighter than a 1200 W fixture, in a 250 W package
- Focuseable black-light
- Variable beam size
- Variable beam control with rotating aerial effects
- Included moon flower effect
- Split color beam effects

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- UV effect
- 7 rotating aerial effects + open
- Film frame effect
- Proportional variable beam angle
- Min/Max beam angle 1.7°/6°
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 612 mm (24.1 in), head straight up
- Weight: 22.5 kg (49.6 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 300/2 FastFit
- Color temperature: 7700 Kelvin
- Color rendering index: 75
- Average lamp life: 750 hours
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet, Artnet to DMX converter
- DMX channels: 18/19
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 2 A at 230 V, 4.4 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port