



# PROLIGHT 2500W (Ref : 2115NT)

The 2500W PROLIGHT combines the advantages of single-ended lamp technology and short focal Fresnel lens to optimise light performance while reducing considerably weight and size. The light gives extremely powerful beam in spot and a smooth, wide spread in flood position. Built to the same rigorous production standards as all LTM products to ensure reliability, ruggedness and longevity, the 2500W PROLIGHT is compatible with both 2,5KW magnetic ballast or 2,5/4KW dimmable electronic ballast



Features
<ul style="list-style-type: none"> <li>- Aluminium mirror</li> <li>- Safety switch for user's protection</li> <li>- Safety glass</li> <li>- MSR 2500W "Daylight" 5600°K bulb</li> <li>- Ø 300mm Fresnel lens</li> <li>- Light focusable : beam angle range 6°/60°</li> </ul>

Photometric Features			
	Distance	Beam	Foot Candles
Spot	20 Ft	2.5	4554
	30 Ft	3.7	2024
	40 Ft	5.0	1139
	50 Ft	6.2	729
Flood	20 Ft	23.1	351
	30 Ft	34.6	156
	40 Ft	46.2	88
	50 Ft	57.7	56

Ballast
<ul style="list-style-type: none"> <li>- 2500/4000W electronic with PFC</li> <li>- 2500W magnetic</li> </ul>

Accessories
<ul style="list-style-type: none"> <li>- MSR 2500W G38 bulb</li> <li>- 4 leaf barndoor</li> <li>- Gel frame</li> <li>- 1/1 single scrim</li> <li>- 1/1 double scrim</li> <li>- 1/2 single scrim</li> <li>- 1/2 double scrim</li> <li>- Alu-cine Black stand</li> <li>- 10 meter head cable</li> </ul>

Head		
Head	12 13/16"	12 7/16"
		Weight: 47,4 lbs.