

Panorama Power MK2



SPECIFICATIONS

- CMY color mixing
- Beam angle: 17° - 134°
- 3 different interchangeable diffusion filters: wide, horizontal and vertical beam
- 4 leaf-barndoor
- Dimmer
- TLT dual lamp system (Exclusive Coemar Patent)
- IP 44 weatherproof rating

PHYSICAL SIZE

- Length: 430 mm (16.93 in)
- Width: 540 mm (21.26 in)
- Height: 760 mm (29.92 in)
- Weight: 47.5 Kg (103.0 lbs)

LAMP AND BALLAST

- Type: 2 x Philips 575 MSR/2
- Color temperature: 7200 Kelvin
- Color rendering index: 80
- Average lamp life: 1000 hours
- Socket: GX 9.5
- 2 electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 6
- Setting and addressing: LEDs display or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 208/230/240 V, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 7 A at 230 V
- DMX data in/out: 3 pin locking XLR

ACCESSORIES

- 360° rotating support for suspension (# 9821)
- Maxi diffuser (# 9822)
- Narrow beam lens (# KIT43)

Panorama Power MK2
9823