

ProSpot 575 MB



SPECIFICATIONS

- 6 colors + open
- 1 aerial wheel, 6 rotating gobos + open
- 1 break-up wheel, 6 gobos + open
- 1 rotating prism
- Focus
- Beam angle 22.5°
- Iris
- Dimmer
- Mechanical strobe, synchronized, random, pulse effect
- Pan 538°, Tilt 252°, 16 bit

PHYSICAL SIZE

- Length: 380 mm (15.0 in)
- Width: 495 mm (19.5 in)
- Height: 635 mm (25.0 in), head straight up
- Weight: 37 kg (81.6 lbs)

LAMP AND BALLAST

- Type: Philips 575 MSR/2
- Color temperature: 7200 Kelvin
- Color rendering index: 80
- Average lamp life: 1000 hours
- Socket: GX 9.5
- Electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 22
- Setting and addressing: LEDs display or remotely

ELECTRICAL SPECIFICATIONS/LIGHT SOURCE

- AC power: 200-208/230/240 V, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 4 A at 230 V, 8 A at 115 V
- DMX data in/out: 3 pin locking XLR

ProSpot 575 MB
9107