

iSpot 1200



iSpot 1200 - # 9130

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- 5 CTO filters
- Proportional frost
- 1 aerial wheel, 6 rotating gobos + open
- 1 break-up wheel, 6 rotating gobos + open
- 2 rotating prisms (with 3D effect)
- Focus
- Proportional zoom 7° - 26°
- Iris
- Dimmer
- Mechanical strobe, synchronized, random, pulse effect
- Pan 530°, Tilt 270°, 16 bit

PHYSICAL SIZE

- Length: 485 mm (19.1 in)
- Width: 505 mm (19.9 in)
- Height: 780 mm (30.7 in), head straight up
- Weight: 50 kg (110.2 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 1200SA/DE
- Color temperature: 6000 Kelvin
- Color rendering index: 85
- Average lamp life: 750 hours
- Socket: SFC 10-4
- Electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 24
- Setting and addressing: led display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 200-208/230/240 V, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 8.2 A at 230 V
- DMX data in/out: 3 pin and 5 pin locking XLR

