

iWash 575



SPECIFICATIONS

- CMY color mixing
- 6 colors + open
- CTO filter
- Beamshaper 180°
- Proportional zoom 9.5° - 34°
- Dimmer
- Mechanical strobe, synchronized, random, pulse effect
- Pan 538°, Tilt 252°, 16 bit

PHYSICAL SIZE

- Length: 380 mm (15.0 in)
- Width: 495 mm (19.5 in)
- Height: 635 mm (25.0 in), head straight up
- Weight: 34.6 kg (76.3 lbs)

LAMP AND BALLAST

- Type: Philips 575 MSR/2
- Color temperature: 7200 Kelvin
- Color rendering index: 80
- Average lamp life: 1000 hours
- Socket: GX 9.5
- Electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 16
- Setting and addressing: LEDs display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 200-208/230/240 V, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 4 A at 230 V, 8 A at 115 V
- DMX data in/out: 3 pin locking XLR

ACCESSORIES

- Maxi diffuser lens kit (#KIT96)

iWash 575 MB
9106