



# THRILL Compact PAR 64 LED

THRILL Compact PAR 64 LED is a bright and powerful LED PAR can that washes your party or event with full, intense and saturated colors. Five 12-watt bright RGB, white, amber and UV LEDs give a uniform field of light that is perfect for warm wall washes, truss toning and front or back lighting. The sit-flat design makes the light easy to slide under tables, tuck inside a truss or into any tight spot.

The THRILL Compact PAR 64 LED features 36 vibrant pre-programmed colors, full RGBWA+UV color mixing so any color in the spectrum can be created and electronic strobe/dimming that make the THRILL Compact PAR 64 LED the safe all-around choice that takes your event from great to brilliant. An included wireless remote control makes programming a breeze, simply point and click to get the color you want or run the pre-programmed settings.

Its lightweight design, super compact profile and wireless remote control make it the perfect fit for on-the-go entertainers, DJs, venues and home enthusiasts that require professional lighting at an affordable price.

Portable, lightweight and easy to control

Sit-flat design allows versatile fixture placement

Plug-and-play functionality with easy-to-use remote control

## FEATURES

- Uniform field of light via 5 x 12 W RGBWA + UV LEDs
- Fixed 18° beam angle
- 36 vibrant pre-programmed colors
- Dynamic effects include color mixing, strobe, dimmer
- Remote control included for quick color selection
- Easy to operate standalone sound-activated, master/slave control methods
- 4 professionally pre-programmed shows
- DMX operable for individualized control and design
- Included multi-function bracket for hanging or surface mount
- Common IEC mains inlet/thru – mains cable included

## TECHNICAL SPECIFICATIONS

### Physical

Length: 262 mm (10.3 in.)

Width: 127 mm (5 in.)

Height: 266 mm (10.4 in.)

Maximum standing footprint: 266 mm (10.4 in) x 204 mm (8 in.)

Weight: 2.1 kg (4.3 lb.)

### Dynamic Effects

Color mixing: RGBWAUV

Color selection: 36 color presets

Electronic dimming: 0-100%

Strobe and pulse effects: Variable speed and action, random strobe

## GALLERY



Electronic 'shutter' effect: Instant open and blackout

#### Control and Programming

Control options: DMX, stand-alone, IR remote control

DMX channels: 6/9

Stand-alone trigger options: Sound-trigger, auto-run

User interface: Control panel with LED display

DMX compliance: ANSI E1.11 - USITT DMX512-A

#### Optics

Light source: 5 x 12 W RGBWAUV LEDs

Minimum LED lifetime: 30 000 hours (to >70% luminous output)\*

Beam angle: 18°

*\*Figure obtained under manufacturer's test conditions*

#### Construction

Housing: High-impact flame-retardant thermoplastic

Color: Black

Ingress protection: IP 20

#### Installation

Mounting: Adjustable bracket, surface or truss mount

Mounting points: Bracket for single rigging clamp, M12 or ½"

Orientation: Any

Location: Dry locations only

#### Connections

AC power in/thru: IEC male inlet/female connector, C14/C13

DMX data in/thru: 3-pin XLR

#### Electrical

AC power: 100-240 V nominal, 50/60 Hz

Fuse: F 3 AL, 250 V

Typical total power consumption: 50 W

Maximum number of fixtures on AC power throughput, 100-130 V: 6 x THRILL Compact

PAR 64 LED or 3 A

Maximum number of fixtures on AC power throughput, 220-240 V: 10 x THRILL

Compact PAR 64 LED or 3 A

*Power consumption figures are typical, not maximum. Allow for +/-10% variation.*

#### Typical Power and Current

110 V, 60 Hz: 0.5 A, 50 W \*

230 V, 50 Hz: 0.3 A, 50W \*

*\*Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%.*

#### Thermal

Cooling: Forced air, temperature-regulated

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Total heat dissipation (calculated, +/- 10%) at full intensity, full white: 170 BTU/hr.

#### Approvals

EU safety: EN 60598, EN 60598-2-17, EN 62471, EN 62493

EU EMC: EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547

US EMC (pending): CFR Title 47 Part 15 Class A

Canadian EMC (pending): ICES-003 Class A

Australia/NZ (pending): RCM

#### Included Items

Power cable, EU, IEC C13 female, molded Schuko, 1.5 m (4.9 ft.)

Power cable, US, IEC C13 female, molded NEMA 5-15P, 1.5 m (4.9 ft.)

Multi-function bracket and hardware

IR remote control, grey, 16-button

Battery for remote control, 3 V, CR2025 lithium

#### Accessories

Super lightweight half-coupler, black: P/N 91602018

Safety cable, SWL 60 kg (132 lb.), BGV C1/ DGUV 17, black: P/N 91604006

#### Related Items

Martin® M-Touch: P/N 90737040

Martin® M-Play: P/N 90737030

#### Ordering Information

THRILL Compact PAR 64 LED: P/N 90280116

