

Specifications

Status Cue Console

Height:	14 cm (5.75 in.)
Width:	104 cm (41 in.)
Depth:	71 cm (28 in.)
Weight:	26.53 Kg (58.5 lbs.)
Power Consumption:	+5 V DC (350 milliampere) for LEDs and +12 V DC (1200 milliampere) for Littlites and logic boards

LinkCard

Size:	full size ISA card
Power Consumption:	2.25 watts

Accessories

The following items are currently available for *Status Cue*:

Item Description Number	Part
<i>Status Cue</i> Console	22020002
<i>Status Cue</i> industrial rack mount 100-MHz Pentium computer, 16-MB memory, CD ROM, one LinkCard, output Y cable, and software	90902020
<i>Status Cue</i> Desktop 100-MHz Pentium Computer, 16-MB memory, CD ROM, one LinkCard, output Y cable, and software	90902021
<i>Status Cue</i> 17-inch color monitor	22040008
LinkCard, output Y cable, and software	22040001
16-MB SIMM	90303074
Music Quest (Opcode) MQX-32M MIDI card	22040002
A/B switchbox db25 for Console	90902014
A/B switchbox db9 for data line	90902011
A/B switchbox db15 for monitor	90902015
Keal road case for Console	22070001
Keal road case for Console, table mount	22070003

Keal road case for two <i>Status Cue</i> rack mount computers, 17" monitor, keyboard, and storage tray	22070002
<i>Status Cue User's Manual</i>	60600028
<i>Status Cue</i> 3-Ring Binder	90901002
Littlite replacement bulb	55030019
Intellipower IQ800 SDI 50/60 UPS w/battery backup (100-250v, 50/60hz)	22040004
10-foot heavy duty data cable w/ Neutrik XLRs	55050005
25-foot heavy duty data cable w/Neutrik XLRs	55050006
50-foot heavy duty data cable w/ Neutrik XLRs	55050007
100-foot heavy duty data cable w/ Neutrik XLRs	55050008

Compliance

The *Status Cue* system is compliant to the following standards:

- EN 60950: 1992
- EN 55022 : 1987 – Class A
- IEC 801-2 : 1991 / prEN 55024-2 : 1992 3kV CD 8kV AD
- IEC 801-3 : 1984 / prEN 55024-3 : 1991 – 3V/m
- IEC 801-4 : 1988 / prEN 55024-4 : 1992 – 0.5 kV Signal Lines, 1 kV Power Lines
- FCC-Class A digital device

