

SPECIFICATIONS

PHYSICAL

Size (L x W x H)..... 340 x 265 x 303 mm (13.4 x 10.4 x 11.9")
Weight..... 7 kg (15.4 lbs.)

THERMAL

Maximum ambient temperature (T_a) 40° C (104° F)
Maximum surface temperature 120° C (250° F)

CONTROL AND PROGRAMMING

Data pin-out pin 1 shield, pin 2 cold (-), pin 3 hot (+)
Control protocol..... USITT DMX-512 (1990)
DMX channels, Destroyer 1/5
DMX channels, Punisher 1/6

AC POWER

Max. power and current 270 W, 1.2 A @ 230 V; 270 W, 2.3 A @ 120 V
Input socket..... 3-prong IEC male socket
Input, 230/245 V model 230/245 V, 50-60Hz
Input, 110/120 V model 110/125 V, 50-60Hz
Primary fuse, 230/245 V model 2.5 AT / 250 V, P/N 05020010
Primary fuse, 110/120 V model 5.0 AT / 250 V, P/N 05020018

INSTALLATION

Minimum distance to combustible materials 0.1 m (4 in)
Minimum distance to illuminated surfaces 0.3 m (12 in)
Minimum clearance around fan and air vents..... 0.1 m (4 in)

ACCESSORIES

MC-1 controller, EU 90718000
MC-1 controller, US 90718100
50 hour lamp, halogen, EHJ, 24V/250W 97000105
300 hour lamp, halogen, EVC (M33), 24V/250W 97000103
G-clamp 91602003
Half-coupler 91602005