

SPECIFICATIONS



PHYSICAL

Length: 330 mm (13.0 in)
Width: 213 mm (8.4 in)
Height: 199 mm (7.8 in)
Weight: 10.4kg (lbs)

SOURCE

Osram HQI-R 150 (included): 150 W, 6000 hr., 4200K

CONTROL

Control options: DMX-512, stand-alone, master/slave
DMX channels: 5
Data I/O: locking 3-pin XLR, pin 1 shield, pin 2 cold (-), pin 3 hot (+)
Recommended cable: ... 24 AWG (min.), low capacitance, 85-150 Ω shielded twisted pair

INSTALLATION

Orientation: horizontal
Minimum distance to combustible materials: 0.1 m (4 in)
Minimum clearance around fan and air vents: 0.1 m (4 in)

AC SUPPLY

Power supply options: 100/120/210/230/250 V, 50/60 Hz (switch-selectable)
Maximum power and current: 205W, 1.9A @ 120V; 195W, 1.0A @ 230V

FUSES

Primary fuse: T 3.15 A, high I^2t , 250 V, P/N 05020013
Secondary fuse: T 2.0 A, 250 V, P/N 05020009

CONSTRUCTION

Housing: sheet steel and aluminum
Finish: black, electrostatic powder coating
Protection factor: IP 20