

appendix c  
**TECHNICAL SPECIFICATIONS**

**Roboscan Pro 1220 CMYR / XR / RPR**

|  |  |
|--|--|
| <b>Dimensions</b>                                |  |
| Length   | 1107 mm (43.6")                            |
| Width (without bracket and handles)              | 316 mm (12.4")                             |
| Width (with bracket and handles)                 | 462 mm (18.2")                             |
| Height (without bracket)                         | 285 mm (11.2")                             |
| <b>Weight</b> CMYR/XR/RPR models                 | 53 kg (117 lb) / 51 Kg (112 lb)            |
| <b>Weight</b> CMYRST/XRST/RPRST models           | 47 kg (103 lb) / 45 Kg (99 lb)             |
| <b>Fuse</b>                                      | 20 AT (6.3 X 32 mm)                        |
| <b>Power consumption</b>                         | 1550 W                                     |
| <b>AC Supply</b>                                 | 100 / 120 / 210 / 230 / 250 V - 50 / 60 Hz |
| <b>Lamp</b> (Type / Wattage / Color Temperature) |  |
| MSR 1200   | Philips MSR 1200 / 1200 W / 5600 K         |
| HMI 1200   | Osram HMI 1200 / 1200 W / 6000 K           |
| <b>Beam angle</b> Pro 1220 CMYR / XR             | 18.5°                                      |
| <b>Beam angle</b> Pro 1220 RPR                   | 12.5°                                      |