

## appendix c

# SPECIFICATIONS

### DIMENSIONS

- Height without mounting bracket ..... 185 mm (7.3")
- Height with mounting bracket ..... 325 mm (12.6")
- Length ..... 533 mm (22.0")
- Width ..... 280 mm (11.1")
- Weight ..... 14 kg (31 lb)

### POWER AND CURRENT CONSUMPTION

- EU model ..... 290 W, 1.3 A at 230 V / 50 Hz
- US model ..... 290 W, 2.4 A at 120 V / 60 Hz
- US Arcstream model ..... 220 W, 2.1 A at 120 V / 60 Hz

### AC VOLTAGE AND FREQUENCY

- EU model ..... 210 V to 260 V, 50 Hz
- US model ..... 95 V to 125 V, 50 Hz / 60 Hz
- US Arcstream model ..... 95 V to 125 V, 60 Hz

### FUSE

- size, all models ..... 5 x 20 mm
- EU model ..... T (time delay) 3.15 A
- US model ..... T (time delay) 6.30 A
- US Arcstream model ..... T (time delay) 3.15 A

### PHILIPS MSD 200 LAMP

- Martin P/N ..... 97010106
- Wattage ..... 200 W
- Color temperature ..... 5600K
- Average life ..... 2000 hrs

### GE LIGHTING ARCSTREAM MBI150/T/40 LAMP

- Martin P/N ..... 97010105
- Wattage ..... 150 W
- Color temperature ..... 4000K
- Average Life ..... 6000 hrs

### OPTICAL

- Beam angle: ..... 11.5°
- Total luminous flux (w/MSD 200) ..... 1250 lm