

SPECIFICATIONS



PHYSICAL

Size without mounting bracket (LxWxH) . . . 312 x 250 x 142mm (12.3 x 9.8 x 14.2in)
Weight 6.5 kg (14.3lb)

CONSTRUCTION

Housing steel and aluminum

THERMAL

Exterior surface temperature under steady state condition 100°C (212°F)
Time required to cool before handling at least 20 minutes
Maximum ambient temperature (T_a) 40° C (104°F)

INSTALLATION

Minimum distance to flammable material 0.3 m (1ft)
Minimum distance to illuminated surface 1.0 m (3.3ft)
Minimum clearance around air vents 0.1 m (4in)

CONTROL AND PROGRAMMING

Stand-alone triggers music or auto

ELECTRICAL

Input 3-prong IEC male socket
AC Power . . switch selectable, operating ranges 115-120 V / 220-240 V, 50-60 Hz
Main fuse 2 AT (time delay),

TYPICAL POWER AND CURRENT

120 V, 50 Hz 115 W, 1.0 A
120 V, 60 Hz 113 W, 0.9 A
230 V, 50 Hz 106 W, 0.5 A
230 V, 60 Hz 105 W, 0.5 A
240 V, 50 Hz 114 W, 0.5 A
240 V, 60 Hz 113 W, 0.5 A

INCLUDED ITEMS - US VERSION

2 m (6.5 ft) US mains cable 18AWG with US male connector (UL approved)
Philips 12V EFP/8H 100W lamp
User manual

INCLUDED ITEMS - NON-US VERSION

3 m (9.8 ft) EU mains cable 3x1.0mm² with Schuko male connector
3 m (9.8 ft) EU mains cable 3x1.0mm² with no male connector
Philips 12V EFP/8H 100W lamp
User manual

ACCESSORIES

Philips 12V EFP/8H 100W lamp P/N 97000004
Half-coupler clamp P/N 91602005
Fuse (2 AT) P/N 05020009

ORDERING INFORMATION

Mania EF2 US version P/N 90430061
Mania EF2 non-US version P/N 90430060