

SPECIFICATIONS

B

PHYSICAL

Size (L x W x H): 296 x 269 x 270 mm (11.7 x 10.6 x 12.1 in)
Weight: 5.5 kg (12.1 lbs)

THERMAL

Maximum ambient temperature (Ta): 40° C (104° F)
Maximum surface temperature: 65° C (149° F)

CONTROL AND PROGRAMMING

DMX-512 (1990) control: 1 / 4 channel, tracking and vector
Stand-alone control: automatic & music trigger, master/slave configurable
Data pinout: 3-pin XLR - pin 1 shield, pin 2 cold (-), pin 3 hot (+)

AC SUPPLY

AC input: 3-pin IEC male socket
Wiring options, "EU" model: 230/245 V, 50-60 Hz
Wiring options, "US" model: 110/120 V, 50-60 Hz
Maximum power and current: 250 W, 1.1 A @ 230 V

FUSES

Primary fuse, EU model: 2.5 AT / 250 V, P/N 05020010
Primary fuse, US model: 5.0 AT / 250 V, P/N 05020018
Secondary fuse: 2.0 AT / 250 V, P/N 05020009

CONSTRUCTION

Housing: UV-resistant fiber-reinforced composite
Finish: black, integral color

INSTALLATION

Minimum distance to combustible materials: 0.1 m (4 in)
Minimum distance to illuminated surfaces: 0.3 m (12 in)
Minimum clearance around fan and air vents: 0.1 m (4 in)

ACCESSORIES

MC-1 Controller, EU: 90718000
MC-1 Controller, US: 90718100
OSRAM 50 h ELC halogen lamp: 97000104
Philips 300 h ELC halogen lamp: 97000106
G-clamp: 91602003
Half-coupler clamp: 91602005